



MiniMag II

The MiniMag™II Intelligent Reader delivers exceptional performance in brilliantly designed housing. It can read up to three tracks of magnetic stripe card data regardless of swiping direction or speed which increases usability. MiniMag's compact footprint is ideal for POS, security, loyalty and other applications where space is limited. The uniquely designed flat surface allows for mounting in different orientations using threaded inserts or Velcro®. The cable can exit through the side or bottom which provides flexibility in mounting options.

MiniMag II

ELECTRICAL

| | |
|---------------------|---|
| Power Requirements: | +5 VDC, ±10%, 50mV ripple maximum Keyboard (PS/2), 40mA maximum RS232, 70mA maximum USB-HID, USB-CDC, and USB-KB, 70mA maximum |
| Interfaces: | Keyboard (PS/2), RS232, RS232 Port Powered, USB-KB, USB-HID, USB- CDC |
| Card Speed: | 5 to 65 ips (7.6 to 165 cm/s) |

ENVIRONMENTAL

| | |
|------------------------|---|
| Operating Temperature: | -40°F to 167°F (-40°C to 75°C) |
| Storage Temperature: | -40°F to 185°F (-40°C to 85°C) |
| Humidity: | Maximum 95% non-condensing, dry storage |

RELIABILITY

| | |
|-----------------|-------------------------------|
| Operating Life: | 1,000,000 card swipes minimum |
| Warranty: | Two years, parts and labor |

MECHANICAL

| | |
|------------------------|---|
| Dimension (L)x(W)x(H): | 3.54 inches (90 mm) x 1.34 inches (34 mm) x 1.10 inches (28 mm) |
| Media Thickness: | 0.015 inches (0.381 mm) to 0.05 inches (1.27 mm) |
| Media Formats: | ISO 7811, AAMVA, and other F2F formats |
| Slot Width: | 0.040 inches (1.37 mm) |
| Swipe Speed: | 3 to 60 inches per second, bidirectional |
| Weight: | 4.6 oz. |
| Indicators: | Tri-colored LED, beeper (excluding on port-powered model) |
| Cable Length: | 6-foot side exit cable (Bottom exit is an option) |
| Cable Connector: | Keyboard - 6 pin mini-DIN, RS232 DB9F |

©2017 International Technologies & Systems Corporation. ID TECH & ViVOPay are registered trademarks of International Technologies & Systems Corporation. MiniMag II and Value through Innovation are trademarks of International Technologies & Systems Corporation. All specifications subject to change without notice. R09/17

UNITED STATES SALES OFFICE

Corporate Headquarters

10721 Walker Street
Cypress, CA 90630
Phone: (714) 761-6368
Toll Free: (800) 984-1010
Fax: (714) 761-8880
sales@idtechproducts.com

INTERNATIONAL SALES OFFICES

Asia

+866-3-326-5988 (Taiwan)
asia@idtechproducts.com.tw

Europe, Middle East & Africa

+44 (0) 1925 269550
emea@idtechproducts.com

ISO 9001 Certified
ISO 14001 Certified

